



SCISSOR LIFT

SLIM ELECTRIC

3232SE^{AC}

Electric Slim Scissor Lift

- Drives at Full Height Indoors Saving Time and Battery Energy Between Overhead Tasks
- Greater Productivity and Lower Cost of Ownership with Outrigger-Free Design
- AC Electric Drive for Extended Duty Cycles, Smoother Controls and Faster Drive Speeds
- Compact Maneuverability from Front Wheel Drive and Steer with Zero Inside Turn Radius
- Fully Proportional Lift and Drive Controls
- Standard Swing Gate
- Easy Serviceability with Swing Out Battery and Power Module Trays
- Maintenance-Free AGM Batteries



**Do More Work by Driving Elevated Between Overhead
Tasks up to 38 ft.**

Standard Features

Work Area

Roll-Out Deck Extension with Incremental Locking Positions
Standard Swing Gate
Lanyard Attachments (4)

Performance

Drive at Full Height Indoors
No Outriggers
AC Electric Drive
Fully Proportional Drive and Lift Controls
Up to 25% Gradeability

Power

Maintenance-Free AGM Batteries
Battery Charge Indicator

Serviceability

Lubrication-Free Scissor Bearings
Easy Maintenance Access to Mechanical and Electrical Components
in a Slide-Out Tray
Logically Grouped Components and Numbered Wiring for Easy Reference

Safety

Dedicated Compartment Protects Electrical and Hydraulic Components
Emergency Shut-Off at Platform and Lower Controls
Non-Skid Metal Deck Construction
Descent Alarm
Drive Speed Interlock
Multi-Axis Tilt Sensor
Scissor Maintenance Lock
Multiple Disc Brakes

Other Features

Leak Containment System® (LCS)
Removable Upper Controls
Voltage-Compensating Fully
Automatic Battery Charger
Fold-Down Guardrails
Hour Meter

Machine Tie Downs
Non-Marking Tires
All Motion Alarm
Fork Lift Pocket
Flashing Beacon (Continuous)

Optional Features

900W Inverter
Tool Tray
Cold Weather Package

Proactive Platform Safety System® (PPSS)
Upper Control Box Supplementary Guard
Pipe Rack
Second Year Extended Warranty



MEC Aerial Work Platforms

3232SE ^{AC}	U.S.	Metric
Heights		
Indoor Working Height*	38 ft.*	11.6 m*
Outdoor Working Height*	30 ft.*	9.1 m*
Indoor Platform Height	32 ft.	9.8 m
Outdoor Platform Height	24 ft.	7.3 m
Stowed Height (Top Guardrail)	96 in.	2.4 m
Stowed Height (Rails Folded)	78 in.	2 m
Stowed Height (Platform Floor)	53 in.	1.3 m
Guardrail Height	43.5 in.	1.1 m
Toeboard Height	6 in.	15 cm
Ground Clearance (Stowed)	4 in.	10 cm
Ground Clearance (Elevated)	0.7 in.	1.8 cm
Dimensions		
Length-Stowed (Overall)	97 in.	2.5 m
Length-Stowed (Ladder Removed)	89.5 in.	2.3 m
Chassis Width	32 in.	81 cm
Platform Length (Extended)	124.5 in.	3.2 m
Platform Length (Retracted)	89.5 in.	2.3 m
Roll-Out Deck Length	35 in.	90 cm
Platform Width	29 in.	74 cm
Wheelbase	74 in.	1.9 m
Total Lift Capacity	550 lbs	250 kg
Personnel Capacity	2 (Indoors); 1 (Outdoors)	
Roll-Out Deck Capacity	250 lbs	113 kg
Speed		
Raise/Lower Speed	52 s / 38 s	
Drive Speed (Stowed)	3 mph	5 km/h
Drive Speed (Elevated)	0.5 mph	0.8 km/h
Performance		
Gradeability	25%	
Turning Radius (Inside)	0 in.	0 m
Weight**	7,145 lbs.	3240 kg
Power Source	24v 240Ah Maintenance-Free Batteries	
Controls	Proportional Drive & Lift Controls	
Tires	15 x 5 in.	38 x 13 cm

*Metric equivalent of working height adds 2m to platform height. U.S. adds 6 ft. to platform height.
**Weight may vary with certain options or configurations.

Important - MEC scissor lifts must be on a hard level surface while elevated.

Warranty - MEC Aerial Work Platforms carry a one (1) year warranty on defective component parts and a five (5) year warranty on defective structural parts. This warranty applies to the original owner only. Consult your MEC dealer for warranty details.

Meets or exceeds the requirements of ANSI A92.20 and CSA B354.6 - 2017.

Specifications subject to change without notice. Photos and diagrams in this brochure are for illustrative purposes only. Contact your MEC distributor for detailed instructions on the proper use and maintenance of this equipment.

Distributed by:



WWW.NLT.COM | 630-782-1000